

8.11 Reguladores de Velocidad

8.11.1 Reguladores electrónicos de velocidad ventiladores monofásicos

Modelo	Escala Bar	Banda Proporc. Bar	Ajuste Fábrica	Montaje	Intensidad	Refrigerante	PVP
					220/230 V.		
P215DP-9101	8 a 14	2,5	10	Pared	8 Amp.	R134a	418,60
P215DP-9100	14 a 24	4	16	Pared	8 Amp	R22, R404A, R407c	418,60
P215DP-9102	22 a 42	6	30	Pared	8 Amp	R410A	418,60
P215ST-9101	8 a 14	2,5	10	Pared	6 Amp	R134a	300,04
P215ST-9100	14 a 24	4	16	Pared	6 Amp	R22, R404A, R407c	300,04
P215ST-9102	22 a 42	6	30	Pared	6 Amp	R410A	300,04
P215SH-9101	8 a 14	2,5	10	Pared	4 Amp	R134a	212,96
P215SH-9100	14 a 24	4	16	Pared	4 Amp	R22, R404A, R407c	212,96
P215SH-9102	22 a 42	6	30	Pared	4 Amp	R410A	212,96
P215LR-9111	8 a 14	2,5	10	Rail DIN	3 Amp	R134a	178,84
P215LR-9110	14 a 24	4	16	Rail DIN	3 Amp	R22, R404A, R407c	178,84
P215LR-9114	22 a 42	6	30	Rail DIN	3 Amp	R410A	178,84
P215LR-9140*	14 a 24	4	16	Rail DIN	3 Amp	R22, R404A, R407c	188,71
P215PH-9200	10 a 25	4	19	Directo	4 Amp	R22, R404A, R407c	-
P215PH-9201	10 a 25	4	11	Directo	4 Amp	R134a	-
P215PH-9202	22 a 42	5	26	Directo	4 Amp	R410A	-
P215PH-9203	10 a 25	4	19	Directo	4 Amp	R22, R404A, R407c	-

* 230 V. entrada Bomba de calor



8.11.2 Reguladores electrónicos de velocidad ventiladores trifásicos

Modelo	Escala Bar	Banda Proporc. Bar	Ajuste Fábrica	Montaje	Intensidad	Refrigerante	PVP
					220/230 V.		
P255MM-9101	8 a 14	0,5 a 4	10	Pared	5	R-134a	-
P255MM-9100	14 a 24	1 a 6	16	Pared	5	R22, R404A, R407c	951,24
P255MM-9503	22 a 42	1 a 8	30	Pared	5	R410A	951,23

8.11.3 Reguladores de velocidad trifásicos para control de condensación

Modelo	Señal Entrada	Tensión Salida	Montaje	Intens. Nominal 400V III 50 Hz	Refrigerante	PVP
VRTMT-12	0-10 V, 4-20 mA	0..99%	pared	12 A.	CFC,HCFC,HFC,NH3	939,80
VRTMT20	0-10 V, 4-20 mA	0..99%	pared	20 A.	CFC,HCFC,HFC,NH3	1.173,70
VRTMT28	0-10 V, 4-20 mA	0..99%	pared	28 A.	CFC,HCFC,HFC,NH3	1.501,53
VRTMT40	0-10 V, 4-20 mA	0..99%	pared	40 A.	CFC,HCFC,HFC,NH3	1.652,34
VRTMT50	0-10 V, 4-20 mA	0..99%	pared	50 A.	CFC,HCFC,HFC,NH3	2.356,12